

# Versa Lift Installation Guide for Treadplate Platform Cover

**CAUTION:** The inside edges of the tread plate cover are sharp! Wear gloves while handling the tread plate cover during installation.

## INSTALLATION OPTION A: Install without bolts.

Although (4) bolts are provided to install the Treadplate to your platform, you may choose to install without bolts:

### Installation After the Lift has been Assembled:

1. Lower the platform to garage floor.
2. Carefully tip the tread plate cover into the platform frame (see Fig. 1).
3. Gently lower the tread plate cover over the platform. The platform should fit completely inside the tread plate cover (see Fig. 1).

**If you have problems with this installation, call Byers Products for more assistance at 405-491-8550.**

## INSTALLATION OPTION B: Install using bolts.

Four 2-1/4" long truss head bolts are provided to install the Treadplate Platform Cover to your Versa Lift:

### Installation During Lift Assembly:

1. Follow the Versa Lift Assembly Guide, except on page 16, substitute Fig. 2 below for Fig. 26. Use the four (4) 2-1/4" bolts supplied with this tread plate cover instead of the 2" bolts normally used to assemble the platform.

### Installation After the Lift has been Assembled:

1. Lower the platform to garage floor.
2. Remove the 8 screws that connect the door panel to the lifting platform as shown in Fig. 28, page 16 of the Versa Lift Assembly Guide.
3. Raise the platform a couple of feet above the floor, then remove the 1/4-20 x 2" screws at the 4 corners of the lifting platform.
4. Carefully tip-in the tread plate cover (Fig. 1).
5. Install the 2-1/4" long truss head bolts provided with this tread plate cover as shown in Fig. 2 below, then tighten the locknuts securely.
6. Lower the platform to the floor and re-connect the door panel using the 8 screws you removed in step 2 above. (Refer to Fig. 28, page 16 of the Versa Lift Assembly Guide.)

Copyright © 2009-2012 Byers Products Group  
All rights reserved. Revised 2010, 2012

