

Remote w/15' Cord

The Versa Lift electric storage lift is designed to move cargo between adjacent floors. The lift's power head mounts over an opening in the upper floor. When ascending, the lifting platform automatically stops level with the upper floor. When descending, the lifting platform automatically stops upon contacting the lower floor. The control switch operation is momentary and the motor brake is applied instantly whenever the switch is released. The platform assembly includes a spring biased door panel that automatically covers the underside of the opening whenever the platform is fully raised. This door is self-adjusting for joists up to 18" in height and can easily be sealed with common weatherstripping.

Installation Requirements:

Opening Required: 22 1/2 x 46 1/2" (+1/4", -0")

Opening Finish: Smooth perpendicular sidewalls

Electrical: 115 vac grounded power outlet

Installation Recommendations:

The Lift's electrical outlet and the attic lighting should preferably be on a single circuit controlled by a switch outside of the attic. The opening should be close enough to the attic ladder so the remote control will reach through the ladder opening. For more detailed information and for specific framing suggestions, see the Rough-In Guide and the Versa Lift Installation Guide.

Specifications:

Control: Hand-held remote with 15' cord & keylock

Floor-to-Floor: 24=8-11', 24H=11-14', 24HX=14-20'

Joist Height Max: 18" (incl. decking & sheet rock)

Lifting Capacity: 15.3 Cu. Ft., 200 lbs. per load

Platform Dimensions: 20-3/4" x 44"

Lift Speed: 8"/sec. (10-ft. in approx. 15 seconds)

Cables (2): .093 steel w/zinc plating 1,000 lb. break

Construction: Powder coated steel

Motor: .6 HP Gear motor with automatic brake


Voltage/Power: 115 vac, 60 hz, 4.5 amps

Power-head Dim.: 26W x 57L x 46.25H


Opening Required: 22 1/2 x 46 1/2" (+1/4", -0")

Opening Finish: Smooth perpendicular sidewalls

Shipping Weight: 165 lbs.





**Versa Lift illustrated in
the raised (UP) position.**






Specification Guide Cont.

Versa Lift Models 24, 24H, 24HX with 15-ft. Corded Remote Control



Versa Lift illustrated in the lowered (DN) position.





Wireless Remote

The Versa Lift electric storage lift is designed to move cargo between adjacent floors. The lift's power head mounts over an opening in the upper floor. When ascending, the lifting platform automatically stops level with the upper floor. When descending, the lifting platform automatically stops upon contacting the lower floor. The control switch operation is momentary and the motor brake is applied instantly whenever the switch is released. The platform assembly includes a spring biased door panel that automatically covers the underside of the opening whenever the platform is fully raised. This door is self-adjusting for joists up to 18" in height and can easily be sealed with common weatherstripping.

Installation Requirements:

Opening Required: 22 1/2" x 46 1/2" (+1/4", -0")

Opening Finish: Smooth perpendicular sidewalls

Electrical: 115 vac grounded power outlet

Installation Recommendations:

The Lift's electrical outlet and the attic lighting should preferably be on a single circuit controlled by a switch outside of the attic. The lift opening does not need to be near the ladder opening. For more detailed information about the opening requirements and for specific framing suggestions, please see the Rough-In Guide and the Versa Lift Installation Guide.

Specifications:

Control: Wireless hand-held remote

Floor-to-Floor: 24W=8-11', 24WH=11-14', 24WHX=14-20'

Joist Height Max: 18" (incl. decking & sheet rock)

Lifting Capacity: 15.3 Cu. Ft., 200 lbs. per load

Platform Dimensions: 20-3/4" x 44"

Lift Speed: 8"/sec. (10-ft. in approx. 15 seconds)

Cables (2): .093 steel w/zinc plating 1,000 lb. break

Construction: Powder coated steel

Motor: .6 HP Gear motor with automatic brake

Voltage/Power: 115 vac, 60 hz, 4.5 amps



Power-head Dim.: 26W x 57L x 46.25H

Opening Required: 22 1/2" x 46 1/2" (+1/4", -0")

Opening Finish: Smooth perpendicular sidewalls



Shipping Weight: 165 lbs.

Versa Lift illustrated in the raised (UP) position.



Specification Guide Cont.

Versa Lift Models: 24W, 24WH, 24WHX with Wireless Remote Control



Versa Lift illustrated in the lowered (DN) position.

